

TYPE CSK-CE BLIND RIVET NUT



Countersunk Head Closed End Rivet Nuts, Round Knurled Body, Steel Zinc

Thread Size	Grip Range	Part No	Hole Diameter +0.1 / -0.0	Body Diameter	Head Diameter	Head Thickness	Overall Length
M3	1.5-3.5	CSK3-CE	5.0	4.9	7.5	1.5	16.0
M3	3.5-5.0	CSK3-5.0-CE	5.0	4.9	7.5	1.5	17.0
M4	1.5-4.0	CSK4-CE	6.0	5.9	8.5	1.5	17.5
M4	4.0-6.5	CSK4-6.5-CE	6.0	5.9	8.5	1.5	20.0
M5	1.5-4.0	CSK5-CE	7.0	6.9	9.5	1.5	20.0
M5	4.0-6.5	CSK5-6.5-CE	7.0	6.9	9.5	1.5	22.5
M5	6.5-9.0	CSK5-9.0-CE	7.0	6.9	9.5	1.5	25.0
M6	1.5-4.5	CSK6-CE	9.0	8.9	11.5	1.5	23.0
M6	4.0-6.5	CSK6-6.5-CE	9.0	8.9	11.5	1.5	25.5
M6	6.5-9.0	CSK6-9.0-CE	9.0	8.9	11.5	1.5	28.0
M8	1.5-4.0	CSK8-CE	11.0	10.9	13.5	1.5	27.0
M8	4.0-6.5	CSK8-6.5-CE	11.0	10.9	13.5	1.5	29.5
M8	6.5-9.0	CSK8-9.0-CE	11.0	10.9	13.5	1.5	32.0
M10	2.0-4.5	CSK10-CE	12.0	11.9	14.5	1.7	30.0
M10	4.5-7.5	CSK10-7.5-CE	12.0	11.9	14.5	1.7	33.0
M10	7.5-10.5	CSK10-10.5-CE	12.0	11.9	14.5	1.7	36.0
M12	2.0-4.5	CSK12	16.0	15.9	19.0	1.9	34.5
M12	4.5-7.5	CSK12-7.5-CE	16.0	15.9	19.0	1.9	37.5
M12	7.5-10.5	CSK12-10.5-CE	16.0	15.9	19.0	1.9	40.5

Dimensions in mm



Closed end rivet nuts prevent the ingress of moisture and contamination into the component and are available in all three head styles. If the sealing of the nut is critical then a dry under head sealant can be applied. The closed end also prevents too long a screw being inserted into the component.

Unit 3 Sandiacre Road, Stapleford, Nottingham, NG9 8EX

☎ 0800 84 99 112 📧 sales@clinchpartsuk.co.uk

Due to continuous development and improvement, specifications may change without prior notification. Please check before specifying.