

## TYPE FLK-ALUM BLIND RIVET NUT



### Flange Head Rivet Nus, Round Knurled Body, Aluminium

Thread Size	Grip Range	Part No	Hole Diameter +0.1 / -0.0	Body Diameter	Head Diameter	Head Thickness	Overall Length
M3	0.5-2.5	FLK3-ALUM	5.0	4.9	7.0	0.8	10.5
M3	2.5-3.5	FLK3-3.5-ALUM	5.0	4.9	7.0	0.8	11.5
M4	0.5-3.0	FLK4-ALUM	6.0	5.9	9.0	1.0	11.0
M4	3.0-4.5	FLK4-4.5-ALUM	6.0	5.9	9.0	1.0	14.0
M5	0.5-2.5	FLK5-ALUM	7.0	6.9	10.0	1.0	13.0
M5	3.0-5.5	FLK5-5.5-ALUM	7.0	6.9	10.0	1.0	16.0
M5	5.5-8.0	FLK5-8.0-ALUM	7.0	6.9	10.0	1.0	19.0
M6	0.5-3.0	FLK6-ALUM	9.0	8.9	12.0	1.5	15.0
M6	3.0-5.5	FLK6-5.5-ALUM	9.0	8.9	12.0	1.5	18.5
M6	5.5-8.0	FLK6-8.0-ALUM	9.0	8.9	12.0	1.5	21.0
M8	0.5-3.0	FLK8-ALUM	11.0	10.9	15.0	1.5	17.0
M8	3.0-5.5	FLK8-5.5-ALUM	11.0	10.9	15.0	1.5	20.0
M8	5.5-8.0	FLK8-8.0-ALUM	11.0	10.9	15.0	1.5	22.5
M8	8.0-10.5	FLK8-10.5-ALUM	11.0	10.9	15.0	1.5	25.0
M10	0.5-3.0	FLK10-ALUM	12.0	11.9	16.0	2.0	19.0
M10	3.0-6.0	FLK10-6.0-ALUM	12.0	11.9	16.0	2.0	24.0
M10	6.0-9.0	FLK10-9.0-ALUM	12.0	11.9	16.0	2.0	27.0
M10	9.0-12.0	FLK10-12.0-ALUM	12.0	11.9	16.0	2.0	30.0
M12	1.0-4.0	FLK12-ALUM	16.0	15.9	22.0	2.0	25.0
M12	4.0-7.0	FLK12-7.0-ALUM	16.0	15.9	22.0	2.0	28.0
M12	7.0-10.0	FLK12-10.0-ALUM	16.0	15.9	22.0	2.0	31.0

Dimensions in mm

Unit 3 Sandiacre Road, Stapleford, Nottingham, NG9 8EX

☎ 0800 84 99 112 📧 sales@clinchpartsuk.co.uk

Due to continuous development and improvement, specifications may change without prior notification. Please check before specifying.