

TYPE FLK-ALUM-CE BLIND RIVET NUT



Flange Head Closed End Rivet Nuts, Round Knurled Body, Aluminium

Thread Size	Grip Range	Part No	Hole Diameter +0.1 / -0.0	Body Diameter	Head Diameter	Head Thickness	Overall Length
M3	0.5-2.5	FLK3-ALUM-CE	5.0	4.9	7.0	0.8	15.0
M3	2.5-3.5	FLK3-3.5-ALUM-CE	5.0	4.9	7.0	0.8	16.0
M4	0.5-3.0	FLK4-ALUM-CE	6.0	5.9	9.0	1.0	16.0
M4	3.0-4.5	FLK4-4.5-ALUM-CE	6.0	5.9	9.0	1.0	19.0
M5	0.5-3.0	FLK5-ALUM-CE	7.0	6.9	10.0	1.0	18.5
M5	3.0-5.5	FLK5-5.5-ALUM-CE	7.0	6.9	10.0	1.0	21.5
M5	5.5-8.0	FLK5-8.0-ALUM-CE	7.0	6.9	10.0	1.0	24.5
M6	0.5-3.0	FLK6-ALUM-CE	9.0	8.9	12.0	1.5	21.5
M6	3.0-5.5	FLK6-5.5-ALUM-CE	9.0	8.9	12.0	1.5	24.0
M6	5.5-8.0	FLK6-8.0-ALUM-CE	9.0	8.9	12.0	1.5	26.5
M8	0.5-3.0	FLK8-ALUM-CE	11.0	10.9	15.0	1.5	26.0
M8	3.0-5.5	FLK8-5.5-ALUM-CE	11.0	10.9	15.0	1.5	28.5
M8	5.5-8.0	FLK8-8.0-ALUM-CE	11.0	10.9	15.0	1.5	31.0
M8	8.0-10.5	FLK8-10.5-ALUM-CE	11.0	10.9	15.0	1.5	33.5
M10	0.5-3.0	FLK10-ALUM-CE	12.0	11.9	16.0	2.0	28.0
M10	3.0-6.0	FLK10-6.0-ALUM-CE	12.0	11.9	16.0	2.0	33.0
M10	6.0-9.0	FLK10-9.0-ALUM-CE	12.0	11.9	16.0	2.0	36.0
M10	9.0-12.0	FLK10-12.0-ALUM-CE	12.0	11.9	16.0	2.0	39.0

Dimensions in mm

Closed end rivet nuts prevent the ingress of moisture and contamination into the component and are available in all three head styles.

Unit 3 Sandiacre Road, Stapleford, Nottingham, NG9 8EX

☎ 0800 84 99 112 📧 sales@clinchpartsuk.co.uk

Due to continuous development and improvement, specifications may change without prior notification. Please check before specifying.