

## TYPE NAL (UNIFIED)

### BLIND RIVET NUT



#### 'US Style' Large Head Rivet Nuts, Round Knurled Body, Steel Zinc

Thread Size	Grip Range	Part No	Hole Diameter +0.1 / -0.1	Body Diameter	Head Diameter	Head Thickness	Overall Length
8-32 UNC	0.5-2.0	NAL8/32	6.75	6.7	9.9	0.75	11.5
8-32 UNC	2.0-3.3	NAL8/32-3.3	6.75	6.7	9.9	0.75	12.7
10-24 UNC	0.5-3.3	NAL10/24	7.6	7.5	10.55	0.75	12.9
10-24 UNC	3.3-5.7	NAL10/24-5.7	7.6	7.5	10.55	0.75	15.5
10-32 UNF	0.5-3.3	NAL10/32	7.6	7.5	10.55	0.75	12.9
10-32 UNF	3.3-5.7	NAL10/32-5.7	7.6	7.5	10.55	0.75	15.5
1/4 UNC	0.7-4.2	NAL1/4-20	10.0	9.9	12.7	0.75	15.5
1/4 UNC	4.2-6.6	NAL1/4-20-6.6	10.0	9.9	12.7	0.75	18.0
5/16 UNC	0.7-3.8	NAL5/16-18	13.5	13.4	17.4	0.9	18.4
5/16 UNC	3.8-7.9	NAL5/16-7.9	13.5	13.4	17.4	0.9	21.3
3/8 UNC	0.7-3.8	NAL3/8-16	13.5	13.4	17.4	0.9	18.4
3/8 UNC	3.8-7.9	NAL3/8-16-7.9	13.5	13.4	17.4	0.9	21.3
1/2 UNC	1.6-5.1	NAL1/2-13	17.5	17.4	22.0	1.2	30.4
1/2 UNC	5.1-8.9	NAL1/2-13-8.9	17.5	17.4	22.0	1.2	34.2
1/2 UNC	8.9-12.7	NAL1/2-13-12.7	17.5	17.4	22.0	1.2	38.0

This US styles rivet nuts has a larger hole and body diameter which can improve the installed performance of the part.

Dimensions in mm

Unit 3 Sandiacre Road, Stapleford, Nottingham, NG9 8EX

☎ 0800 84 99 112 ✉ sales@clinchpartsuk.co.uk